



lampade alogene bispina UV-STOP Long life

bispina rinforzate G4

*Conforme alla CEI EN 60061-1 foglio n. 7004-59-6



PIN Ø 0,75 mm

bispina rinforzate GY6,35

*Conforme alla CEI EN 60061-1 foglio n. 7004-59-6



PIN Ø 1,25 mm

Durata 2.000 ore

UV-STOP



Volt	Watt	Attacco	Dim.	Luminosità lm
6	5	G4	9x30	50
	10	G4	9x30	100
	15	G4	9x30	230
12	10	G4	9x30	120
	20	G4	9x30	300
	35	G4	9x30	600
14*	20	G4	9x30	350
24	10	G4	9x30	100
	20	G4	9x30	350
28*	10	G4	9x30	140
	20	G4	9x30	350
6	50	G6,35	11x44	910
12	75	GY6,35	11x44	1.500
24	35	GY6,35	11x44	650
	50	GY6,35	11x44	950
	100	GY6,35	11x44	2.000
	150	GY6,35	13x44	3.200
	200	GY6,35	13x44	3.800
	250	GY6,35	13x44	5.000

*per uso nautico

Codice	Classe energetica
420 2989	C
420 2900	C
420 2950	C
420 3010	C
420 3015	C
420 3020	C
420 3018	C
420 3022	C
420 3025	C
420 3027	C
420 3028	C

Codice	Classe energetica
420 3042	C
420 3110	C
420 3120	C
420 3125	C
420 3135	C
420 3140	C
420 3142	D
420 3145	D

SATINATE

Volt	Watt	Attacco	Dim.	Luminosità lm
12	10	G4	9x30	100
	35	G4	9x30	535
	20	G6,35	11x44	350
	50	G6,35	11x44	950

Codice	Classe energetica
**420 3210	D
**420 3220	D

Codice	Classe energetica
**420 3225	D
**420 3245	D

**Articoli in PHASE OUT, disponibili fino a esaurimento scorte.

Confezione 100 pz. Confezione mini con sovrapprezzo 20%. (Solo per prodotti a stock).